

AF MODEL ADD SERIES VISCOUS PRODUCTS WEIGHT FILLING MACHINE



Filling Into 1 Liter Tin Can



Filling Into 5 Liters Tin Can



Filling Into 20 Liters Tin Can

- NEW TECHNOLOGY
新技术
- EASY TO OPERATE
操作简便
- HIGH ACCURACY
高精度
- HIGH FILLING OUTPUT
高填充输出
- SELF-DIAGNOSE
FUNCTION
自我诊断功能



AF AdvanTech (s) Pte Ltd
61, Bukit Batok Crescent, #04-02 Heng Loong Building, Singapore.
TEL : +65 6896 6380 FAX : +65 6896 6381
E-mail : sales@afadvantech.com.sg Website : www.afadvantech.com.sg

模型 MODEL ADD-1P-30K-TS 半自动粘性液体产品重量设定灌装机型

This AF Model ADD Series Semi-Auto Weight Filling Machine is one of the most intelligent and advance filler that enable to fill from 1 kg to maximum 30kg packaging size. Full parameter and memories setting to allow "One Touch" to re-call pre-setting value and control etc...

Most ideal to fill viscous fluid such as paint, lacquers, lotions, shampoo, cosmetic and conditioner.

Ex-proof version available upon request.

该半自动系列重量灌装机型是最聪明和高新技术之一，填充从1公斤到最大三十公斤。

全参数和记忆设定让“单键”重新呼叫预先设定值和控制等..

适宜的液体填充范围如：涂料，油漆，乳液，洗发水，化妆品和护发粘性液体等等..

防爆功能的机器为客户的要求。

TECHNICAL SPECIFICATIONS 技术规格

Filling Range	灌装范围	: 1 to 30kg 公斤
Filling Output	灌装输出	: 1kg ~ 700 Tins/Hr, 5kg ~ 450 Tins/Hr, 18kg ~ 170 Tins/hr Viscosity Range ~ 1000 to 5000cps @ 25° ~ 40° C Temperature
Filling Accuracy	灌装精度	: 1kg (±5grams), 5kg (±10grams), 18kg (±20grams)
Contact Part	接触部分	: Stainless Steel 不锈钢 304
Power Supply	电源	: 240Vac, Single Phase 50/60Hz (Depends on Country Setting)
Air Supply	压缩气源	: 6 bar at 0.2m³/hour

Note: Specifications and Picture shown are subject to change for improvement without notice.

注：规格和图片显示如有变更，恕不另行通知改善。

AF MODEL ADD SERIES VISCOUS PRODUCTS WEIGHT FILLING MACHINE



模型 **MODEL ADD-2P-SS-EX-TS** 半自动粘性液体产品重量设定灌装机型

This AF Model ADD Series Semi-Auto Ex-proof 2 Nozzles Weight Filling Machine designed to fill Flammable Fluid. Suitable for Class 1 Zone 1 environment operation. Double nozzles increase filling output and built-in with "No Tin Can No Fill" safety feature. Most ideal to fill viscous fluid such as solvent based paint, lacquers and alcohol based products.

该自动对焦模式地址系列半自动防爆两个喷嘴头重灌装机充满易燃液体。

适用于1区一类防爆环境的作用。双喷嘴增加填充输出和内置的“无容器无填充”安全功能。

最为理想流体，以填补如溶剂型涂料，油漆和酒精制品为主

TECHNICAL SPECIFICATIONS 技术规格

Filling Range	灌装范围 : 1 to 5kg 公斤
Filling Output	灌装输出 : 1kg ~ 900 Tins/Hr and 5kg ~ 650 Tins/Hr Viscosity Range ~ 1000 to 5000cps @ 25° ~ 40° C Temperature
Filling Accuracy	灌装精度 : 1kg (±5grams) and 5kg (±10grams)
Contact Part	接触部分 : Stainless Steel 不锈钢 304
Power Supply	电源 : 240Vac, Single Phase 50/60Hz (Depends on Country Setting)
Air Supply	压缩气源 : 6 bar at 0.2m³/hour

Sales Office

AF AdvanTech (S) Pte Ltd

61 Bukit Batok Crescent #04-02 Heng Loong Building Singapore 658078

Tel: +65 6896 6380 Fax: +65 6896 6381

Email: sales@afadvantech.com.sg

Website: www.afadvantech.com.sg



Note: Specifications and Picture shown are subject to change for improvement without notice.

注: 规格和图片显示如有更变, 恕不另行通知改善。